



World leader in vehicle  
de-pollution technology



## SEDA HV Battery Discharger

N-527753

### consisting of:

- Stainless steel case
- PTC heating element
- Voltage & current display screen
- Powerful fan
- Disconnecter

### Your benefits:

- Safe and easy to use
- Efficient discharging
- Compact in design



Safe module discharge on  
SEDA HV-battery Dismantling  
Table with Extinguishing Pool

### Safe discharge option for critical lithium-ion batteries



Discharging of Li-ion batteries is an integral part of the recycling process as it decreases the voltage of batteries & reduces the risk of an operator getting an electric shock during further battery treatment. It is possible to discharge battery modules up to 100 V with discharging capacity up to 4,5 kW. At the end of total discharging short-circuiting of modules must be performed. After 72-hour quarantine of discharged modules, they must be checked by a HV-technician. In case of no signs of a thermal reaction, the discharged modules can be defined as non-critical.

Advantage: non-critical modules enable cutting transport costs as there is no more need of ADR-transporting.



### TECHNICAL DETAILS

**Dimensions:** 220 x 434 x 165 mm  
**Voltage:** 100 V  
**Discharge cap.:** 4 kW

### ORDER INFORMATION

**N-527753** SEDA Battery  
Discharger



Leading Company  
of Austria



### SEDA-Umwelttechnik GmbH

Schwendter Str. 10 / 6345 Kössen / Tirol / Österreich  
UID-Nr.: ATU56621622 / FB-Nr.: FN 231790 v / FB-Gericht: Innsbruck  
Certified company according to DIN EN ISO 9001

**P:** +43 5375 6318-0  
**F:** +43 5375 6318-9  
**E:** info@seda.at  
**W:** www.seda-international.com