Technical specification sheet

HBC050A30 (excl. battery) | Battery Cutter

Specifications		
article number		101.003.173
model		HBC050A30 (excl. battery)
blade type		30 standard
cutter type		Battery
short description		Battery Cutter
battery included		no
connectivity, mobile app		Bluetooth
max. working pressure	bar/Mpa	500 / 50
max. cutting opening	mm	170
max. cutting force	kN/t	438 / 44.7
protection rate		IP57
sound emission @ 1m/3.25ft	dB(A)	75
sound emission @ 4m/13ft	dB(A)	66
required oil content (effective)	cc	155
hydraulic oil type		ISO-L HV VG 36
weight, ready for use	kg	15.3
dimensions (LxWxH)	mm	814 x 266 x 278
temperature range	°C	-20 +55
weight (excl. battery)	kg	13.8
max. cutting diameter round bar (S235 acc. to EN 10025-2)	mm	22
max. cutting diameter round tube (E235 acc. to EN 10305-1) based on wall thickness 3mm/0,12in.	mm	60
catalytic converter	%	90
number of cuts per day		50
number of operating hours per day		4



Technical drawing dimensions		
dimension A	mm	814
dimension B	mm	266
dimension C	mm	278

© Holmatro 2026-03-20
While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.